

Circular Saw LXT®

DHS680

18V • 5 000 min⁻¹ • 165 mm

Efficient and compact brushless professional saw

An efficient brushless and cordless circular saw for wood. Accepts blades with 165 mm diameter that achieve a max. cutting depth of 57 mm. Ventilation air is guided through the front to keep the cut line clear and an LED light offers added illumination. Compatible with a guide rule.



LXT **BL** **ADT**
MOTOR

Technical specifications

Nominal Battery Voltage	18 V
Voltage LXT	✓
Max. Cutting Depth at 90°	57 mm
Max. Cutting Depth at 45°	41 mm
Max. Cutting Depth at 50°	37 mm
Max. Bevel Range (Left)	0 / 50 °
No load speed	5000 min ⁻¹
Sound Power Level (L _{WA})	105 dB(A)
Sound Pressure Level (L _{pA})	94 dB(A)
Noise Uncertainty (K Factor)	3 dB(A)
Vibration Level (3 axes)	≤ 2,5 m/s ²
Vibration Uncertainty (K Factor)	1,5 m/s ²
Tool weight with battery	3,0 - 3,3 kg
Product Dimensions (L x W x H):	350 x 170 x 238 mm
Brushless Motor	✓

User benefits

- LED light illuminates the work site
- Battery protection system automatically shuts off power when the battery level is low
- The rubber coating on the handle ensures a firm working grip
- Removable dust extraction connection

Link to product - www.makitauk.com



Related products

Optional AC

164095-8

Parallel Guide

194385-5

Clamp set

196961-1

Dust Nozzle 35 / 40 Mm

199140-0

Guide rail, 1 000 mm

783203-8

Hex Wrench 5 Mm

838182-6

MakPac (3) Inlay

BL1820B

Battery LXT® 2,0 Ah

BL1840B

Battery LXT® 4,0 Ah

BL1860B

Battery LXT® 6,0 Ah



194367-7

Guide rail, 3 000 mm



196953-0

Guide rail adapter



198885-7

Guide rail joint connector set, 2 pcs



199826-6

Quick-Release Ratcheting Guide Rail



821551-8

Makpac case (3)



B-32910

Circular Saw Blade T.C.T, 165 x 20



BL1830B

Battery LXT® 3,0 Ah



BL1850B

Battery LXT® 5,0 Ah



E-05664

Guide Rail Protective Holder

Other

[User manual](#)

[Parts drawing](#)